





## 19N430

# Product Technical Information LDPE extrusion coating product

## **Applications**

19N430 is a versatile extrusion coating resin. This homopolymer is suitable for multipurpose extrusion coating applications. 19N430 coated substrates such as paper, board and aluminium can be used for packaging food and liquids, powders, medical devices, agricultural materials, chemicals and many other products. It shows an improved heat sealability compared to 23L430.

19N430 is also suitable for injection moulding of flexible products.

## **Benefits and Features**

19N430 is an additive free low density ethylene homopolymer. Its special polymer structure gives the following properties:

- Good processability
- High coating speed
- Good draw down ability with low neck in and stable web edges
- Low fumes during extrusion
- Good organoleptical properties
- Good adhesion on many substrates
- Very good heat sealing properties
- High purity and very low gel level


We recommend that you consult your INEOS technical representative for further advice on the use of 19N430.

Properties	Test Method	Value	Units
Physical			
Melt flow rate	ISO 1133	7.5	$g/10 \min$
Condition D			
Conventional density	ISO 1183 Method D	920	$kg/m^3$
(conditioning ISO 1872/1)			
Vicat softening temperature*	ISO 306 Method A	88	°C
DSC melting temperature (10°C/min)	<b>INEOS Method</b>	108	°C
Shore hardness D*	ISO 868	47	-
Tensile strength @ yield*	ISO R527	9	MPa
Tensile strength @ break*	ISO R527	10	MPa
Elongation @ break*	ISO R527	550	0/0

INEOS Polyolefins









- Data should not be used for specification work
- \* Measurements made on compression moulded plaques

#### **Extrusion conditions**

19N430 can be processed on commercial extrusion coating equipments over the melt temperature range 280-325°C. Coating weights as low as 7 g/m<sup>2</sup> can be obtained at extrusion rates normally used for common substrates.

## Storage

19N430 should be stored in a dry and dust free environment at temperatures below 50°C. Exposure to direct sunlight should be avoided, as this may lead to product deterioration.

### **Regulatory Information**

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, send an email to <a href="mailto:psnohreg@innovene.com">psnohreg@innovene.com</a>. Unless specifically indicated, the products mentioned herein are not suitable for applications in the medical or pharmaceutical sector.

#### Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained from the website <a href="https://www.ineospolyolefins.com">www.ineospolyolefins.com</a>. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

## **Exclusion of Liability**

Although INEOS POLYOLEFINS endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS POLYOLEFINS is accurate and up to date, no representation or warranty, express or implied is made by INEOS POLYOLEFINS as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS POLYOLEFINS are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS POLYOLEFINS materials are suitable for the particular purpose intended and INEOS POLYOLEFINS shall not be responsible for any loss or damage caused by misuse of INEOS POLYOLEFINS products. To the maximum extent permitted by law, INEOS POLYOLEFINS accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS POLYOLEFINS materials or the use of INEOS POLYOLEFINS materials in conjunction with such other materials.

