



HSPB BH3910

YUPLENE BH3910 is an ultrahigh impact propylene copolymer designed for injection molding and compounding applications. YUPLENE BH3910 has excellent properties in impact strength as well as stiffness, flow, mechanical properties and heat resistance, which make YUPLENE BH3910 suitable for auto parts, electric appliances, large size containers, thin wall and very high speed injection applications.

Application
Injection Molding / automobile applications
industrial parts for electronic, large container

Characteristics
High Impact strength, High flowability

Physical Properties

	Value	Unit	Test Method
Melt Index	60	g/10min	ASTM D1238
Softening Point (Vicat)	150	°C	ASTM D1525
Tensile Strength at Yield	180	kg/cm ²	ASTM D638
Elongation at Break	<200	%	ASTM D638
IZOD Impact Strength (Notched, 23°C)	>50(N.B.)	kg-cm/cm	ASTM D256
Flexural Modulus	8000	kg/cm ²	ASTM D790
Hardness(Rockwell)	80	R Scale	ASTM D785
Heat Distortion Temperature	110	°C	ASTM D648

These are typical properties only, and are not to be construed as specific limits.

Head Office 99 Seorin-dong, Jongno-gu, Seoul 110-110, Korea
Tel. 82-2-2121-7332 Fax. 82-2-2121-6909
SK Institute of 140-1 Woncheon-dong, Yuseong-gu, Taejeon, Korea
Technology Tel. 82-42-609-8621 Fax. 82-42-609-8603
Online www.skglobalchemical.com
www.skchem.com

ISO 9001 Certified

