

GY-130

Polypropylene (Homopolymer)



Product Description

GY-130 is a polypropylene homopolymer designed for stretched products such as flat yarn. It is a low flow rate resin with a middle molecular weight distribution.

Key Features

- Excellent stretchability
- Excellent machinability

Applications

- Flat yarns (T-die type) for woven bags, tape and rope

Typical Properties

	Item	Measuring Method	Value	Unit
Physical	Melt Flow Index (230°C, 2.16kg)	ASTM D1238	3.5	g/10min
	Density	ASTM D1505	0.9	g/cm ³
Mechanical	Tensile Stress (Yield)	ASTM D638	330	kgf/cm ²
	Tensile Strain (Break)	ASTM D638	> 500	%
	Flexural Modulus	ASTM D790	15,000	kgf/cm ²
	Notched Izod Impact Strength (23°C)	ASTM D256	4	°C
Thermal	Heat Deflection Temp. (4.6kgf/cm ²)	ASTM D648	109	°C

• NOTE : These are not to be construed as specifications



www.lottechem.com

*Disclaimer : All information in this document is for reference only and is not a final product specification. The content of this document is not legally binding and suitability issues regarding final use must be determined by the user, and the user alone is responsible for the outcome. The values and information specified in this document may change without prior notice for quality enhancement of the product.