

Acran Boğaziçi Kimya A.Ş. Mahmutbey Mah. (İstoç Tic. Merk) 2412 Sk. (C Plaza) No:2 İç Kapı No : 56,57,58 / Bağcılar İstanbul

Technical data sheet Metallocene Polyethylene CAST FILM Produced in Europe

# **Product Description**

Lumicene $^{\ensuremath{\mathbb{R}}}$  mPE M1835 is designed for high performance cast stretch film for mono and multi-layer film production.

Lumicene<sup>®</sup> mPE M1835 is a Metallocene based Low Density Polyethylene with hexene as comonomer.

Lumicene<sup>®</sup> mPE M1835 brings:

- High stretchability (up to 350%) in cast stretch film
- Oustanding Impact and Puncture Resistance
- Excellent Holding Force
- Very good Processability on small and large cast lines
- Very low gel level

Lumicene<sup>®</sup> mPE M 1835 is also suitable for other applications such as Surface Protection, Food Packaging, Hygiene Film and Cast Films. It exhibits an excellent blending-ability with LDPE and LLDPE was observed.

### Characteristics

Property	Method	Unit	Typical value
Density	ISO 1183	g/cm³	0.918
Melt Flow Rate (190°C/2.16 kg)	ISO 1133	g/10 min	3.5
Melting temperature	ISO 11357	°C	108.5
Vicat temperature	ISO 306	°C	99

Values indicated are typical for this product. Density and MFR are properties routinely measured during "the standard quality control procedure". The other figures are generated by tests not included in the "standard quality control procedure", and are given for information only. Data are not intended for specification purposes.

### Processing

On a cast film line Lumicene  $^{^{(\!R\!)}}$  mPE M1835 can be easily extruded in the following conditions:

- Melt Temperature: 220 to 280°C
- Chill roll temperature: 20 to 80°C

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



Acran Boğaziçi Kimya A.Ş. Mahmutbey Mah. (İstoç Tic. Merk) 2412 Sk. (C Plaza) No:2 İç Kapı No : 56,57,58 / Bağcılar İstanbul

**vo:2 ©** 0 (212) **659 94 37 ● www.acran**.com.tr **Lum®Cene®<sup>94</sup>thPE® M##835**<sup>n.tr</sup>

Technical data sheet Metallocene Polyethylene CAST FILM Produced in Europe

## **Additives**

Antioxidant : yes PPA : no

### **Cast film properties**

These values have been measured on a 20 µm cast film.

Property	Method	Unit	Typical value (*)
Tensile Strength at Yield MD/TD <sup>(**)</sup>	ISO 527-3	MPa	7/6.4
Tensile Strength at Break MD/TD <sup>(**)</sup>	ISO 527-3	MPa	36/39
Elongation at Break MD/TD <sup>(**)</sup>	ISO 527-3	%	385/588
Elmendorf MD/TD <sup>(**)</sup>	ISO 6383-2	N/mm	116/176
Dart test	ISO 7765-1	q	711
Нате	ISO 14782	9 %	27
Gloss 45°	ASTM D2457	70	80.7

(\*) Figures stated here above are obtained using laboratory test specimens produced at the following extrusion conditions: die gap = 250  $\mu$ m, chill roll temperature = 20°C, throughput = 7 kg/h, melt temperature = 260 °C

(\*\*) MD : Machine Direction, TD : Transverse Direction

### Handling and storage

Please refer to the safety data sheet (SDS) for handling and storage information. It is advisable to convert the product within one year after delivery provided storage conditions are used as given in the SDS of our product. SDS may be obtained from the website: www.totalrefiningchemicals.com

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.